

## Designed for comfort, tactility and gripping delicate instruments

- Soft, elastic latex material provides exceptional comfort
- Thin, lightweight design for enhanced tactile sensitivity
- Textured fingers enable easier handling of small objects and delicate tools
- Complies with FDA food handling requirements
- Also available in vend pack (except EMEA)



### Industries

- Life Sciences
- Food Processing
- Chemical

### Recommended For

- Sample taking and processing
- Testing
- Vehicle maintenance
- Food contact
- All food processing, applications that have food contact
- Food processing and handling
- Meat, Fish and Food Processing
- Secondary food processing



## TECHNICAL DATA SHEET

### PRODUCT INFORMATION

	<b>69-318</b>
<b>Material</b>	Natural Rubber Latex
<b>Color</b>	Natural
<b>Glove Design</b>	Chlorinated, Powder-Free, Textured Fingers
<b>Cuff</b>	Beaded
<b>Manufacturing/QMS Audit Standards</b>	ISO 9001:2008
<b>Regulatory/Standards Compliance</b>	Category III, EAC TP TC 019:2011, EN ISO 374-1:2016, EN 420:2003 + A1:2009, EN ISO 374-5:2016, EN 374:2003, EN 374:2003, FDA21 CFR 177-2600, ISO 9001, ISO 13485
<b>Packaging</b>	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
<b>Storage</b>	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
<b>Country of Origin</b>	Malaysia
<b>User Needs Segment</b>	Multi-Purpose
<b>Available sizes</b>	XS (5.5 - 6), S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10)
<b>Sensitisers</b>	<ul style="list-style-type: none"> <li>Zinc Diethyldithiocarbamate (ZDEC)</li> <li>Zinc Dibutyldithiocarbamate (ZDBC)</li> </ul> <p><i>Only a very small number of users may be sensitized to this ingredient in the glove and hence may develop irritant and/or allergic contact reactions.</i></p>

### PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.5		ASTM D3767,EN420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.12 / 4.7		ASTM D3767,EN420
Finger Thickness (mm/mils)	0.14 / 5.5		ASTM D3767,EN420
	<b>BEFORE AGING</b>	<b>AFTER AGING</b>	
Ultimate Tensile Strength (MPa)	≥ 18	≥ 14	ASTM D412 & D573
Elongation at Break (%)	≥ 650	≥ 500	ASTM D412

## TECHNICAL DATA SHEET

### ORDERING INFORMATION

Size	L (8.5 - 9)	M (7.5 - 8)	S (6.5 - 7)	XL (9.5 - 10)	XS (5.5 - 6)
<b>Ansell Product Code</b>	69318090	69318080	69318070	69318100	69318060

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
Riverside Business Park  
Blvd International, 55  
1070 Brussels, Belgium  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

#### Asia Pacific Region

Ansell Global Trading Center  
(Malaysia) Sdn Bhd  
Prima 6, Prima Avenue  
Block 3512, Jalan Teknokrat 6  
63000 Cyberjaya  
Selangor, Malaysia  
T: +603 8310 6688  
F: +603 8310 6699

#### North America Region

Ansell Healthcare Products LLC  
111 Wood Avenue South,  
Suite 210  
Iselin, NJ 08830, USA  
T: +1 800 800 0444  
F: +1 800 800 0445

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.  
Blvd. Bernardo Quintana No. 7001-C,  
Q7001 Torre II,  
Suites 1304, 1305 y 1306,  
Col. Centro Sur, c.p. 76079  
Queretaro, Qro. Mexico  
T: +52 442 248 1544 / 248 3133


#### Australia

Ansell Limited  
Level 3,678 Victoria Street,  
Richmond, Vic, 3121  
Australia  
T: +61 1800 337 041  
F: +61 1800 803 578

#### Russia

Ahcenn PYC  
123610 Poccnr, Mockba  
Kpachonpechehckar  
Ha6. 12, n.3, op. 1304A  
Ten. +7 495 258 13 16

### Performance Standards and Regulatory Compliance



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2020 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.