

## **Product Information**

## ISO Class 5 - 8

Cleanroom Class 100 – 100,000 EU Grade B/C/D

# Durx® 770

## 55% Cellulose / 45% Polyester Nonwoven Cleanroom Wiper

Durx® 770 is a cellulose / polyester nonwoven wiper recommended for ISO Class 5 and above environments composed of a hydroentangled nonwoven blend of 55% cellulose and 45% polyester.

This combination of properties provides Durx® 770 with the level of absorbency, abrasion resistance and chemical compatibility required for controlled environments and applications. Durx® 770 is further

enhanced with an ultra-low particle and fiber treatment to significantly reduce particles and fibers compared to Durx® 670.



#### **Key Attributes**

- 55% cellulose / 45% polyester hydroentangled nonwoven blend
- · Enhanced with an ultra low particle and fiber treatment

#### **Benefits**

- Excellent combination of the synthetic polyester strength and cleanliness with the absorbent characteristics of cellulose
- Reduced particle and fiber generation with ultra low particle and fiber treatment
- · Smooth, absorbent and durable
- · Low extractable levels
- · Chemically compatible with common cleaning and disinfecting solutions
- Autoclavable
- Economical

#### **Applications**

- Designed for use in ISO Class 5 and higher cleanroom environments
- Facilities manufacturing integrated circuit, printed circuit board and electronic components
- General equipment wrap and wipe downs
- General purpose wiping applications
- Cleaning of lab equipment
- General wiping in component prep, compounding and wash areas
- Applying and removing cleaning and disinfecting solutions

## Other ISO Class 5 and above nonwoven wipers

- BlueSorb® 750
- Durx® 670
- MicroFirst<sup>®</sup>
- MicroFirst LP®
- ProjX® 700
- Pro-Wipe® 750
- Pro-Wipe® 880
  ValuClean® Plus

#### **Pre-Wetted Option**

The same wiper material can be provided in pre-wetted formats for reduced VOC emissions, increased convenience, increased productivity, improved solvent control and cleaning protocol repeatability and reduced costs.

#### Sterile Validated Option

For aseptic processing areas, the same wiper material can be provided in a gamma irradiated validated sterile to a 10<sup>-6</sup> sterility assurance level. Dry and pre-wetted versions available.

### www.Berkshire.eu.com

Contact: Tel 44 (0) 870 757 2877 enquiries@berkshire.uk.com

| America | Tel 1 413 528 2602      | Fax 1 413 528 2614      | info@berkshire.com         |
|---------|-------------------------|-------------------------|----------------------------|
| Europe  | Tel 44 (0) 870 757 2877 | Fax 44 (0) 870 757 2878 | enquiries@berkshire.uk.com |
| SE Asia | Tel 65 6252 4313        | Fax 65 6252 4312        | enquiries@berkshire.com.sg |
| Japan   | Tel 81 3 5827 2380      | Fax 81 3 5827 2382      | master@berkshire.co.jp     |



#### **Technical Data:**

| Attribute            |                  | Units                  | Value | Test Method  |
|----------------------|------------------|------------------------|-------|--|
| Basis Weight         |                  | g/m²                   | 65.8  | TAPPI T-410  |
| Caliper              |                  | μm                     | 245   | TAPPI T-411  |
| Fibers               | ≥100µm           | fibers/cm <sup>2</sup> | 17    | IEST-RP.CC004.3, Sec 6.1.3 / Sec 6.2.2               |
| Particles            | ≥0.5µm           | x10³/cm²               | 5.0   | IEST-RP.CC004.3, Sec 6.1.3 / Sec 6.2.1               |
| Sorbency             | Capacity         | mL/m²                  | 258   | IEST-RP.CC004.3, Sec 8.1 modified / Sec 8.2 modified |
|                      | Efficiency       | mL/g                   | 3.9   |  |
|                      | Rate             | seconds                | 3     |  |
| Non-Volatile Residue | DI Water         | g/m²                   | 0.10  | IEST-RP.CC004.3, Sec 7.1.2                           |
|                      | IPA              | g/m²                   | 0.049 |  |
| Ions                 | Na <sup>+</sup>  | ppm                    | 83    | IEST-RP.CC004.3, Sec 7.2.2                           |
|                      | K <sup>+</sup>   | ppm                    | 9.3   |  |
|                      | Ca <sup>++</sup> | ppm                    | 31    |  |
|                      | Mg <sup>++</sup> | ppm                    | 12    |  |
|                      | CI-              | ppm                    | 52    |  |

#### Notes:

- Technical data represented in this table are typical values at the time of publication. These should not be used as product specifications.
- Due to differences in test methods applied and equipment utilized by different wiper manufacturers, valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions
- Third party testing can be performed upon request

#### **Order Information**:

| Product   | Number        | Size             | Shts/pk | Pks/cs | Style   |
|-----------|---------------|------------------|---------|--------|---------|
| Durx® 770 | DR770.0404.10 | 4x4" (10x10cm)   | 1200    | 10     | Stacked |
| Durx® 770 | DR770.0404.40 | 4x4" (10x10cm)   | 300     | 40     | Stacked |
| Durx® 770 | DR770.0707.12 | 7x7" (18x18cm)   | 300     | 12     | Stacked |
| Durx® 770 | DR770.0909.20 | 9x9" (23x23cm)   | 300     | 20     | Stacked |
| Durx® 770 | DR770.1212.20 | 12x12" (30x30cm) | 150     | 20     | Stacked |
| Durx® 770 | DR770.1818.10 | 18x18" (45x45cm) | 150     | 10     | Stacked |

## Other Berkshire Products



Wipers



**Glove Liners** 



**Mop Systems** 



**Documentation Systems** 



**Face Masks** 



Swabs

## www.berkshire.eu.com

Contact: Tel 44 (0) 870 757 2877 enquiries@berkshire.uk.com