

Lab-Tips® ESD Swab-LT070PESD

Small ESD Swab with Pointed Tip

Cleanroom laundered 100 ppi open cell foam sock swab

The LTO70PESD swab with pointed head features an efficiency. The small tapered handle and rigid tip ESD safe handle, engineered with static dissipative polymer. Its laundered open cell foam head combines superior cleanliness with particle entrapment capability. Its ridged head design further enhances cleaning.

provide maximum control.



Key Attributes

- Cleanroom laundered polyurethane foam over rigid tip
- 100 ppi open cell foam
- Static dissipative polypropylene handle with thermally bonded head
- Laundered and packaged in ISO Class 4 (Class 10) cleanroom

Benefits

- Low particles, fibers, ions and extractables
- Good chemical resistance
- Soft and non-abrasive with no contaminating adhesives
- Free from Silicone, amides and DOP
- Ridged surface for improved cleaning ability
- Packaged in an anti-static bag.

Environmental

Complies with RoHS and REACH requirements

Applications

- Designed for the highest level of contamination control in critical processing applications
- Applying lubricants, adhesives or other liquids
- Removing excess materials
- Static-sensitive applications

Physical Characteristics

Head Material	Open Cell Foam	Handle Thickness	2.5mm {0.098"}	
Head Width	4mm {0.157"}	Handle Length	50mm {1.97"}	
Head Thickness	4mm {0.157"}	Total Swab length	70mm {2.75"}	
Head Length	20mm {0.787"}	Head Bond	Thermal	
Handle Material	Polypropylene	Handle Text	Berkshire	
Handle Width	2.5mm {0.098"}			

Other Foam sock tip swabs

- · LTO1465ESD Long handle
- · LTO70RESD Small handle rigid head swab

www.berkshire.com Contact: Tel 1 800 242 7000 BC_5100_12-2014

Americas	Tel 1 413 528 2602	Fax 1 413 528 2614	info@berkshire.com
Europe	Tel 44 (0) 870 757 2877	Fax 44 (0) 870 757 2878	enquiries@berkshire.uk.com
SE Asia	Tel 65 6252 4313	Fax 65 6252 4312	enquiries@berkshire.com.sg
Japan	Tel 81 3 5827 2380	Fax 81 3 5827 2382	master@berkshire.co.jp



Technical Data:

ATTRIBUTE		LT070PESD	TEST METHODS	
Surface Resistivity of Handle	ohms/sq	1.0 x 10 ⁸	ANSI/ESD STM 11.13	
Non-Volatile Residue	IPA mg/swab	0.054	IEST-RP.CC004.3, Sec 7.1.2	
Ions (μg/swab)	Chloride	0.014	IEST-RP.CC004.3, Sec 7.2.2	
	Sulfate	0.026		
	Nitrate	ND*		
	Phosphate	ND*		
	Fluoride	ND*		
	Potassium	0.0053		
	Calcium	0.029		
	Sodium	0.0039		
	Magnesium	0.0021		

Notes:

- Data shown are typical values
- Due to differences in test methods applied and equipment utilized by different swab manufacturers, valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
- * ND* = below the detection limit of the equipment.

Order Information:

Product	Part Number	Size	Swabs/Pk	Pks/Cs	Case size
Small ESD Foam w/ Pointed Tip	LT070PESD.20	70mm	100	20	235 x 105 x 85mm

For more information on our other contamination control products or technical consultation, please contact your Berkshire Sales Representative or e-mail: info@berkshire.com

Other Berkshire products

For information on our other products, please click on the relevant text.



Wipers



Glove Liners



Mop Systems



Documentation Systems



Face Masks



<u>swaps</u>