

# Vikan cleaning system

## recommended for Dycem flooring

This double bladed squeegee provides effective agitation and removal of liquid from Dycem flooring systems.

### SPECIFICATION

- Aluminium handle, 1310mm long
- Revolving neck floor squeegee, with double foam lip
- Replaceable black squeegee blade
- Recommended for use with **Inspec N10** detergent solution
- Alternatively, this product can be used in conjunction with other **Dycem** approved benefits

### BENEFITS

- All raw materials are fully FDA compliant
- In accordance with EU Commission Regulations, this product is recommended for use within food preparation areas, without limitation
- The handle, with the attached item, should reach the chin of the user, helping to prevent occupational back injuries
- The handle is autoclavable, and can withstand temperatures up to 120°C
- The replaceable cassette can be cleaned in temperatures up to 100°C
- The squeegee blade has a dual function, eliminating the need for a squop
- The Vikan product is extremely easy to disassemble
- The squeegee is double bladed, providing effective removal of both water and debris from floors and other surfaces
- The squeegee cassette can be easily detached (as illustrated), for cleaning or replacement

### DIRECTIONS FOR USE

1. Hold the trigger of the Inspec N10 spray upright, or at a slight angle, and spray the Dycem surface liberally with the detergent solution
2. Cover the entire area and leave for approximately thirty seconds to allow the detergent to act on the residue
3. Agitate the Dycem surface using the Vikan squeegee
4. Remove any excess liquid with the Vikan squeegee blade

It is recommended that the squeegee blade is replaced every 2-3 months, unless otherwise directed by customer specific SOP.

