

# TECHNICAL DATASHEET

REV.00

## 611S00000



### FEATURES:

- Sterilizable in autoclave with steam and with gamma and beta radiations
- Frame constructed of a special material, resistant to several cycles of sterilization
- New elastic strap in antistatic silicone
- Innovative quick elastic band adjustment system
- Available with direct and indirect ventilation
- New Anti-Fog121 coating available
- RX insert available

### FEATURES FRAME:

Frame Typology	<b>Mask</b>
PPE field of view	<b>&gt;40°</b>
Complete PPE weight (g)	<b>128</b>
Size (mm)	<b>154</b>
Frame Features	<b>TPR</b>
Elastic Band Features	<b>Silicon</b>
Ventilation System	<b>Vented</b>

### FEATURES OCULARS/LENSES:

VLT% (+/-5%)	<b>88.2</b>
Material Ocular/Flip-up	<b>Polycarbonate</b>
Colour	<b>Clear</b>
Technical Treatment	<b>-</b>
Thickness [mm](+/- 0.1)	<b>2.25</b>
Curvature	<b>Base 5,0 Cylindric</b>
Optical Class	<b>1</b>
UV Protection	<b>380 nm</b>
Spare parts	<b>lens : 042060</b>

### MARKS:

Standard Reference	<b>EN166 EN170</b>
Frame Marking	<b>U EN166 BT 2C-1.2 CE</b>
Ocular/Flip-up Marking	<b>2C-1.2 U 1 BT CE</b>

### FIELDS OF EMPLOYMENT

Protection against high-speed particles - medium energy (B); Protection against high-speed particles at extreme temperatures (T);

Notes