Page 130 sur 368

HEAVY WEIGHT	Superior absorption capacit	y for pollutions treatment	
		* WARNING : it concerns only hydrophobic products	
WHY USE POLYPROPYLENE ABSORBENTS?			
Polypropylene absorbents provide:		The use and disposal of Polypropylene absorbents saves	

Polypropylene absorl

- Exceptional absorbency (up to 25 times their own weight)

- Selective absorption : 3 types available (Oil Selective - General Purpose -

Chemical) allowing you to absorb almost any liquid.

rbents saves you time and money:

- Quick and easy to deploy, saving you time

- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money

- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

No specific risk. For further information, please refer to the material safety data sheet. SECURITY:

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment. SCHOELLER INDUSTRIES SAS-Z.I. rue de la Mazière F-67130 WISCHES - Tél 03 88 47 35 00 / Fax 03 88 47 06 79 www.schoellerindustries.fr - info@schoellerindustries.fr



TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

APPLICATION

ideal for areas of high foot traffic or even fork lift truck movement.

Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic

Products have a non-porous bottom layer and also have a reinforced top surface making them

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.



Bag of 1 Mat 1.20X30M

GREY HYDROPHILIC

SMF

MATS

MICR



ARTICLE CODE

GM313-D

fluids, coolants, mineral oil, solvents, water, etc...).

Oil absorption capacity L/KG*:	150
Water absorption capacity L/KG*:	117
Net weight:	16,668
Qty / pallet:	8

NDUST Fabricant leader européen d'absorbants nontissés pour l'environnement et l'industrie

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

ARCTCOEMPC

SI