

# TECHNICAL DATA SHEET



## PURE POLYPROPYLENE SORBENT



ARTICLE CODE


# GR211-D

Oil absorption capacity L/KG*:	<b>144</b>
Water absorption capacity L/KG*:	<b>80</b>
Net weight:	<b>9,984</b>
Qty / pallet:	<b>15</b>

\*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M lenght perforated 40 cm and cross 50 cm

## APPLICATION

<b>GREY HYDROPHILIC</b>	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
<b>SM</b> 	Products are reinforced on one side to give the product durability.
<b>ROLLS</b>	Rolls are ideal for day today housekeeping and can for example be used pro-actively to catch drips from the underside of conveyors, used to stop liquids from being tracked from one area to another or line the top of a work bench.
<b>HEAVY WEIGHT</b>	Superior absorption capacity for pollutions treatment

**\* WARNING : it concerns only hydrophobic products**

## WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

## ADDITIONAL INFORMATION

**TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

**SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.

**STORAGE:** Store in a dry and cool place.

**DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

## SPECIAL REMARKS

*The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.*

SCHOELLER INDUSTRIES SAS- Z.I. rue de la Mazière F-67130 WISCHES - Tél 03 88 47 35 00 / Fax 03 88 47 06 79 www.schoellerindustries.fr - info@schoellerindustries.fr