SI



TECHNICAL DATA SHEET			
	PURE POLYPROPYLENE SORBENT  Schoeller  ARTICLE CODE  GS1		125 72 8 12 apacity is calculated in EDANA norm : putting O cill bath at 35°C until
Box of 20 Socks 7.5CMX1.20M			
APPLICATION			
GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc).		
FLOCKS	Lose fiber to provide high absorption		
SOCKS	Contain liquids at the base of leakymachinery and stop it spreading into other areas or use to contain spilt liquids.		
FLOCKS	Primarily used to absorb "deeper" spills in spill response applications		
	* V	VARNING : it concerns only	v hydrophobic product

\* WARNING : it concerns only hydrophobic products

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)

- Selective absorption : 3 types available (Oil Selective - General Purpose -

Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time

- No dust or mesh to clean-up, saving you time

- They ensure the floor is slip free when used pro-actively, saving you money

- Unlike granules its easy to see how much you are using, saving you money

- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

## ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

## SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safetv and health of employees and customers and the protection of the environment. SCHOELLER INDUSTRIES SAS– Z.I. rue de la Mazière F-67130 WISCHES – Tél 03 88 47 35 00 / Fax 03 88 47 06 79 www.schoellerindustries.fr

10/11/2016 11:39:55