

Technical Data



Property		unit	SPEC
Material		-	Polyester
Length	MD	mm	400±10
	TD	mm	400±10
Weight		g/sh	27.8±2.8
		g/m ²	168±17
Thickness		μm	580±20
Time to sorption	HORI.	sec/5Φ	≤ 4
	VERTI.	sec/5cm	≤ 60
Absorbency		g/sh	≥ 59.2
		g/m ²	≥ 370
APC	≥ 0.3 μm	ea/sh, 1cfm	≤ 160
LPC	0.5 μm	ea/m ²	≤ 315
Lint	≥ 100μm	ea/sh	≤ 35

Basic Info

Description

WW-3016 is Class 10 Cleanroom Wiper applied with Thermal cutting to minimize the particle generation on edges.

Using the specially weaved 100% Polyester prevents from the generation of Particle and Fiber and improves the absorbency and wipe ability.

WW-3016 is produced in special cleaning facilities And with Cleaning Know-how.

Product Environment

- Laundered and Packaged in the Cleanroom
- The quality of the product is guaranteed from the manufacturing stage through shipping
- Cleanroom is continually managed for maximum customer satisfaction
- Using De-ionized water to minimize ions and Particles
- Utilizing U/F system to reduce the number of particles (above 0.3μm) less than 50 per ml.

Application

- Wiper for Cleanroom

Features

- Minimizes Particles, NVR and Ion contents
- Special process for better wipe and absorption capacity
- Double-wrapped to prevent contamination
- High absorbing rate and capacity

Anseong Office

348-1 Boche, Miyang,
Anseong, Gyeonggi,
Korea
Tel 031-678-8800
Fax 031-678-8899

Anseong Factory

269-2 Kyereuk, Miyang,
Anseong, Gyeonggi,
Korea
Tel 031-678-8900
Fax 031-678-8960

Pyeongchang Factory

516-5 Jujin,
Pyeongchang,
Gangwon, Korea
Tel 033-333-6660
Fax 033-332-9287

Anseong Logistics

348-1 Boche, Miyang,
Anseong, Gyeonggi,
Korea
Tel 031-678-8700
Fax 031-678-8720

China Suzhou

No.38 Phoenix Mountain
Rd. Dongshan Town,
Suzhou city, Jiangsu
Tel 0512-6639-7463
Fax 0512-6639-7161