

PRODUCT SPECIFICATION

Product name:

semperguard® vinyl powdered

Spec code:

VXS-048CL-N-3CZ

Date of issue:

28-Aug-2017

Type
Labelling
Shape
Material
Colour
Inner
Outer
Cuff/surface
Storage life

single use disposable protective glove, non sterile
all information on dispenser box
ambidextrous - straight fingers
Polyvinylchlorid (PVC) [not made with natural rubber latex]
transparent
pre-powdered
no treatment
rolled cuff/smooth
5 years

Available sizes
S (6-7)

M (7-8) L (8-9) XL (9-10)

Min. thickness [in mm]	Finger	Palm	Cuff
single measured	0.045	0.065	0.040
double measured	0.09	0.13	0.08

	Before aging	After aging	Testing method
Elongation	min. 300 %	min. 300 %	ASTM D5250
Tensile strength	n.a.	n.a.	n.a.

AQL (for pinholes)	≤ 1.5	EN 374-2 EN 455-1
Residual powder / Powder content	≤ 10 mg/glove	EN 455-3
Force at break	median ≥ 3.6 N	EN 455-2
Length	median 240 mm	EN 455-2

Storage instructions

Store according to ISO 2230:2002. Ensure that the area is kept cool, dry and dust free, avoid ventilation and storage close to photocopy equipment. Copper-ions discolour the glove. Protect gloves against ultraviolet light sources, as sunlight and oxidizing agents. Storage above 30°C will lead to accelerated aging and should be avoided.

Page 1/2

semperguard® vinyl powdered

VXS-048CL-N-3CZ_Version E_August 2017_EN

Replaces all previous versions and valid for 2 years after date of issue

Standards, guidelines & quality certificates

Quality certification	ISO 9001 ISO 14001 OSHAS 18001
Conformity to directives	Personal Protective Equipment 89/686/EEC: Cat I for minimal risks
Confomity to standards	EN 420
	ASTM D5250
Conformity to food regulation	1935/2004 (EC) 10/2011 (EU)
	Suitable for food contact up to 2 hours at 40°C except fatty food-stuff for which food simulants D1 and D2 acc. to EC Reg. 10/2011 apply.
labelling according to	EN 420

Warning and reporting system

Potentially allergenic ingredients

not known

For further information, the actual version of the ingredients list is given on request.

Authorized signatory/

Product management

Regulatory affairs

C. Eichler

A. Scharl

J. Glantschnig

Page 2/2

semperguard® vinyl powdered

VXS-048CL-N-3CZ_Version E_August 2017_EN

Replaces all previous versions and valid for 2 years after date of issue