

## **Characteristics**













Applications



Less than 10

ohms

Included



- ULPA Filter With an efficiency of 99.999% on 0.12 micron. Tested: IEST RP-CC001.3. Filtration efficiency of 99.9995% on 0.18 micron. Tested: IEST RP-CC001.3. U15 by MPPS method as per EN 1822. All of our ULPA Vacuum Cleaners are Aerosol Leak Tested before leaving our facility - Included
- \*Cleanroom compatible with ISO Class 4 (former Class 10). Can be used in the pharmaceutical industry
- Static Free and ESD Safe
- EMI/RFI Shielded
- TELECOM package available
- 4-stage Filtration System includes an ULPA Filter (U15), Double Cloth Filter and Disposable Filter Bags. An internal OSHA compliant HEPA Filter (H14) is available as an optional 5th stage of filtration
- Designed for use in Contamination Controlled **Environments**
- Powerful dual speed thruflow motor
- For dry recovery only
- Made entirely of chrome-polished steel
- Mounted on a 4-wheel dolly for easy maneuverability
- Includes a complete tool kit

## **Specifications**


EMI-CWR	110110B	110110C	110110D	110110E
Type (Powerhead)	Electric	Electric	Electric	Electric
Voltage	240 V	240 V	240 V	240 V
Hertz	50 Hz	50 Hz	50 Hz	50 Hz
Phase	Single	Single	Single	Single
Wattage	1000 W	1000 W	1000 W	1000 W
Power	1 kW	1 kW	1 kW	1 kW
Amperage	4.6 amps.	4.6 amps.	4.6 amps.	4.6 amps.
Air Flow	204 m <sup>3</sup> /h			
Vacuum Pressure	2410 mm H <sub>2</sub> 0			
Sound Level	70 dB(A)	70 dB(A)	70 dB(A)	70 dB(A)
Plug Type	European	UK	Swiss	Chinese
Suction Inlet	38 mm	38 mm	38 mm	38 mm
Cart Type	4 Wheel Dolly (4W)			
Filter Cleaning	None	None	None	None
Dry Recovery - Tank	15.1 L	15.1 L	15.1 L	15.1 L
Dry Recovery - Disposable Filter Bag	9.5 L	9.5 L	9.5 L	9.5 L
Length	38 cm	38 cm	38 cm	38 cm
Width	43 cm	43 cm	43 cm	43 cm
Weight (Vacuum Only)	16 kg.	16 kg.	16 kg.	16 kg.
Height	71 cm	71 cm	71 cm	71 cm
Cord Length	10.6 m	10.6 m	10.6 m	10.6 m

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



EMI-CWR Tools and Accessories with Disposable Filter Bags - Included



EMI SUPPRESSION / RFI SHIELDING



ULPA Filter - Included

Tel: ((39) 051 79.53.52) Fax: ((39) 051 4695077) Website: http://www.tiger-vac.eu Email: info@tiger-vac.it