

Isis Stool

(ISI-4-CR)



Stool height: 570—820 mm

Height range: 250 mm

Seat diameter: 380mm

Glides: ESD black polyamide glide

Conductivity: $R = 10^4 \text{ Ohm}$

Standards: EN 12527, EN 12528, EN 12529
DIN EN ISO 14001 : 2005

Load capacity: 50 kgs

Vinyl: Black conductive

Electrically conductive,
antistatic
 10^4 to 10^6 Ohms

Flame retardant according to
EN 1021/Part 1 & 2

Options:

Castors—ESD brake unloaded

Castors—ESD brake loaded

Isis Stool (ISI-5-CR)



Stool height: 490—680 mm

Height range: 190 mm

Seat diameter: 380mm

Glides: ESD black polyamide glide

Conductivity: $R = 10^4 \text{ Ohm}$

Standards: EN 12527, EN 12528, EN 12529
DIN EN ISO 14001 : 2005

Load capacity: 50 kgs

Vinyl: Black conductive

Electrically conductive,
antistatic
 10^4 to 10^6 Ohms

Flame retardant according to
EN 1021/Part 1 & 2

Options:

Castors—ESD brake unloaded

Castors—ESD brake loaded

Isis Stool (ISI-6-CR)



Stool height: 440—565 mm

Height range: 125 mm

Seat diameter: 380mm

Castors: ESD Soft tyre
brake unloaded

Conductivity: $R = 10^4$ Ohm

Standards: EN 12527, EN 12528, EN 12529
DIN EN ISO 14001 : 2005

Load
capacity: 50 kgs

Vinyl: Black conductive

Electrically conductive,
antistatic
 10^4 to 10^6 Ohms

Flame retardant according to
EN 1021/Part 1 & 2

Options:

ESD Glides
Castors—ESD brake loaded