



● STR-1-CR



● STR-2-CR



● STR-3-CR

Dimensions	Sitting Height :
Back : 400 x 420(h) mm	STR-1-CR : 605-855 mm
Seat : 465 x 465 mm	STR-2-CR : 530-730 mm
	STR-3-CR : 460-590 mm



## Technical Specifications

Chair Base :	Five star polished base with epoxy powder coated underside - Diametre 620 mm
HEPA Filter :	P2
Footring :	Chrome footring with polished ring and black epoxy powder coated underside - Diametre 460 mm Fully Adjustable
Castors/Glides :	Manufactured in accordance with DIN EN 12 528, ANSI BIFMA x 5.1 Leakage resistance $\leq 10\%$ Ohms measured with 100V dc Load per castor 100N (DIN 51953)
Mechanism :	Independent seat and back tilt with back height adjustment
Loading Limit :	Gaslift maximum working limit 150 Kgs Castors/glides working limit 50 Kg each



## Upholstery

Black Conductive Vinyl

Flammability :	BS EN 1021-1:1994 (Cigarette) BS EN 1021-2:1994 (Match) BS 7176:1995 Medium / Low Hazard BS 5852:1990 Section 4
Resistivity :	BS EN 100015-1:1992

All chairs are manufactured in the UK and in accordance with ISO 9002 Quality Assurance Standard, they are also tested to the stringent BS5459:1990Part 2 To test level 'S' (Severe)