



STRATOS ESD



● STR-1-ESD



● STR-2-ESD



● STR-3-ESD

Dimensions

Back : 400 x 420(h) mm
Seat : 465 x 465 mm

Sitting Height :

STR-1-ESD : 605-855 mm
STR-2-ESD : 530-730 mm
STR-3-ESD : 460-590 mm



Technical Specifications

Chair Base :	Five star polished base with epoxy powder coated underside - Diametre 620 mm
Footring :	Chrome footring with polished ring and black epoxy powder coated underside - Diametre 460 mm Fully Adjustable
Castors/Glides :	Manufactured in accordance with DIN EN 12 528, ANSI BIFMA x 5.1 Leakage resistance $\leq 10\% \text{ Ohms}$ measured with 100V dc Load per castor 100N (DIN 51953)
Mechanism :	Independent seat and back tilt with back height adjustment
Loading Limit :	Gaslift maximum working limit 150 Kgs Castors/glides working limit 50 Kg each



Upholstery

24/7 ESD / Hi-Tech Fabric

Flammability : BS EN 1021-1:1994 (Cigarette)
BS EN 1021-2:1994 (Match)
BS 7176:1995 Medium / Low Hazard
BS 5852:1990 Section 4

Resistivity : BS EN 100015-1:1992

All chairs are manufactured in the UK and in accordance with ISO 9002 Quality Assurance Standard, they are also tested to the stringent BS5459:1990Part 2 To test level 'S' (Severe)